



MITTAL
Hotmax



Electric **Deck Oven**
Gas **Deck Oven**
Rolling **Machine**
Spiral **Mixer**

Electric Deck Oven



Basic 1/40



Basic 2/40



Basic 1/50 Vetro



Basic 2/50 Vetro



Basic 4



Basic 44



Tray 4



Tray 44



Tray 6 L



Tray 66 L



Tray 9



Tray 99



Electric Deck Oven

Model	Basic 1/40	Basic 2/40	Basic 1/50 Vetro	Basic 2/50 Vetro	Basic 4	Basic 44	Tray 4	Tray 44	Tray 6 L	Tray 66 L	Tray 9	Tray 99
Temperatura °C	50 320	50 320	50 500	50 500	50 500	50 500	50 500	50 500	50 500	50 500	50 500	50 500
Power supply VOLT	230	230	230 400	230 400	230 400	230 400	230 400	230 400	230 400	230 400	230 400	230 400
Chamber n°	1	2	1	2	1	2	1	2	1	2	1	2
Power KW	1,6	2,4	5	7,5	4,7	9,4	6,9	13,8	10,2	20,4	15,3	30,6
Top heating element power W	800x1	800x2	2500x1	2500x2	2350x1	2350x2	1150x3	1150x6	1700x3	1700x6	2550x3	2550x6
Bottom heating element power W	800x1	800x1	2500x1	2500x1	2350x1	2350x2	1150x3	1150x6	1700x3	1700x6	2550x3	2550x6
External Dimension cm	L 56,8 P 50,0 H 28,0	L 56,8 P 50,0 H 43,0	L 91,5 P 69,0 H 35,7	L 91,5 P 69,0 H 52,7	L 97,5 P 92,4 H 41,3	L 90,0 P 87,1 H 74,5	L 110,0 P 107,4 H 41,3	L 110,0 P 107,4 H 74,5	L 150,0 P 107,4 H 41,3	L 150,0 P 107,4 H 74,5	L 150,0 P 131,4 H 41,3	L 150,0 P 131,4 H 74,5
Internal Dimension cm	L 41,0 P 36,0 H 9,0	L 41,0 P 36,0 H 9,0	L 62,0 P 50,0 H 12,0	L 62,0 P 50,0 H 12,0	L 66,0 P 66,0 H 14,0	L 66,0 P 66,0 H 14,0	L 82,0 P 84,0 H 17,5	L 82,0 P 84,0 H 17,5	L 123,0 P 84,0 H 17,5	L 123,0 P 84,0 H 17,5	L 123,0 P 108,0 H 17,5	L 123,0 P 108,0 H 17,5
Packing dimensions cm	L 67,0 P 60,0 H 41,0	L 67,0 P 60,0 H 58,0	L 97,0 P 77,0 H 44,5	L 97,0 P 77,0 H 61,5	L 102,0 P 102,0 H 54,5	L 102,0 P 102,0 H 87,5	L 118,0 P 118,0 H 54,3	L 118,0 P 118,0 H 87,5	L 158,0 P 118,0 H 54,3	L 158,0 P 118,0 H 87,5	L 158,0 P 142,0 H 54,3	L 158,0 P 142,0 H 87,5
Volume m3	0,16	0,23	0,33	0,46	0,57	0,91	0,76	1,22	1,01	1,63	1,22	1,96
Net weight kg	23,0	33,0	40,0	73,6	76,0	120,6	103,5	164,0	127,0	225,0	174,0	323,5
Gross weight kg	23,0	33,0	43,0	78,5	84,0	130,0	116,0	177,0	144,3	243,5	197,0	348,0

Gas Deck Oven



Gas 4



Gas 6



Gas 9

Gas Deck Oven

Model	Gas 4	Gas 6	Gas 9
Temperatura °C	0 450	0 450	0 450
Power supply VOLT	230	230	230
Power KW	16,1	21,5	27
Gas consumption Kg/h m3/h m3/h	1,262 (G 30/31) 1,693 (G 20) 1,693 (G 25)	1,696 (G 30/31) 2,275 (G 20) 2,275 (G 25)	2,129 (G 30/31) 2,852 (G 20) 2,852 (G 25)
External Dimension cm	L 100,0 P 106,2 H 56,0	L 100,0 P 136,2 H 56,0	L 130,5 P 136,2 H 56,0
Internal Dimension cm	L 62,0 P 62,0 H 15,0	L 62,0 P 92,0 H 15,0	L 92,0 P 92,0 H 15,0
Packing dimensions cm	L 103,5 P 94,0 H 59,0	L 103,5 P 125,5 H 59,0	L 133,5 P 122,5 H 59,0
Volume m3	0,57	0,77	0,96
Net weight kg	112,0	135,0	164,0
Gross weight kg	127,0	143,0	173,0

Rolling Machine

Rolling Machine

Model	DMA 310/1	DMA 500/1	DMA 310/2
Dough weigh gr	80 210	210 700	80 210
Pizza diameter cm	14 30	26 45	14 30
Power supply volt	230 1 ph 50 Hz	230 1 ph 50 Hz	230 1 ph 50 Hz
Single-phase motor power KW hp	0,25 0,33	0,25 0,33	0,25 0,33
External Dimension cm	L 48,0 P 33,5 H 43,0	L 65,0 P 34,5 H 43,0	L 48,0 P 33,5 H 45,0
Internal Dimension cm	L 75,5 P 40,5 H 50,7	L 75,5 P 40,5 H 50,7	L 75,5 P 40,5 H 50,7
Volume m3	0,16	0,16	0,16
Net weight kg	18,0	27,0	22,0
Gross weight kg	22,0	31,0	26,0



DMA 310/1



DMA 310/2



DMA 500/1



DSA 310 / 420



DSA 310/420 T GO



DSA 420/500 RP

Rolling Machine

Model	DSA 310	DSA 310 T.GO	DSA 420 T.GO	DSA 420 T.RP	DSA 500 RP
Dough weigh gr	80 210	80 210	210 700	220 1000	220 1000
Pizza diameter cm	14 30	14 30	26 40	26 40	26 45
Power supply volt	230 1 ph 50 Hz	230 1 ph 50 Hz	230 1 ph 50 Hz	230 1 ph 50 Hz	230 1 ph 50 Hz
Single-phase motor power KW hp	0,25 0,33	0,25 0,33	0,25 0,33	0,25 0,33	0,25 0,33
External Dimension cm	L 47,5 P 37,5 H 66,0	L 47,5 P 37,5 H 66,0	L 58,5 P 43,5 H 79,0	L 58,5 P 43,5 H 71,5	L 66,5 P 43,5 H 71,5
Internal Dimension cm	L 55,5 P 45,0 H 71,0	L 55,5 P 45,0 H 71,0	L 67,5 P 50,5 H 83,5	L 67,5 P 50,5 H 83,5	L 75,0 P 54,0 H 77,5
Volume m3	0,18	0,18	0,28	0,28	0,31
Net weight kg	30,0	30,0	36,0	38,0	41,0
Gross weight kg	36,0	36,0	43,0	45,0	48,4

Spiral Machine



Spiral Machine												
Model	IBM 5	IBM 10	IBM 15	IBT 15	IBM 20	IBT 20	IBM 30	IBT 30	IBM 40	IBT 40	IBM 50	IBT 50
Dough weigh kg	5,0	8,0	12,0	12,0	17,0	17,0	25,0	25,0	35,0	35,0	42,0	42,0
Capacity	7,0	10,0	16,0	16,0	22,0	22,0	32,0	32,0	41,0	41,0	48,0	48,0
Dough/ hour kg	29,0	35,0	48,0	48,0	56,0	56,0	88,0	88,0	112,0	112,0	128,0	128,0
Bowl diameter cm	24,0	26,0	32,0	32,0	36,0	36,0	40,0	40,0	45,0	45,0	45,0	45,0
Power supply volt	230	230	230 400	230 400	230 400	230 400	230 400	230 400	230 400	230 400	230 400	230 400
Single-phase motor power KW (volt230) hp	0,37 0,5	0,37 0,5	0,75 1,0	0,75 1,0	0,75 1,0	0,75 1,0	1,1 1,5	1,1 1,5	1,1 1,5	1,1 1,5	1,5 2,0	1,5 2,0
Single-phase motor power KW (volt400) hp	- -	- -	0,75 1,0	0,75 1,0	0,75 1,0	0,75 1,0	1,1 1,5	1,1 1,5	1,1 1,5	1,1 1,5	1,5 2,0	1,5 2,0
Machine sizes Dimension cm	L 26,0 P 50,0 H 50,0	L 24,0 P 50,0 H 50,0	L 38,5 P 67,0 H 72,5	L 38,5 P 67,0 H 72,5	L 38,5 P 67,0 H 72,5	L 38,5 P 67,0 H 72,5	L 42,4 P 73,5 H 80,5	L 42,4 P 73,5 H 80,5	L 48,4 P 80,5 H 82,5	L 48,4 P 80,5 H 82,5	L 48,0 P 80,5 H 82,5	L 48,0 P 80,5 H 82,5
Packing dimensions cm	L 62,5 P 39,5 H 70,5	L 62,5 P 39,5 H 70,5	L 73,5 P 41,5 H 79,5	L 73,5 P 41,5 H 79,5	L 73,5 P 41,5 H 79,5	L 73,5 P 41,5 H 79,5	L 76,5 P 47,5 H 88,5	L 76,5 P 47,5 H 88,5	L 82,5 P 54,0 H 93,5	L 82,5 P 54,0 H 93,5	L 82,5 P 54,0 H 93,5	L 82,5 P 54,0 H 93,5
Volume m3	0,17	0,17	0,24	0,24	0,24	0,24	0,32	0,32	0,42	0,42	0,42	0,42
Net weight kg	41,0	42,0	65,0	65,0	65,0	65,0	86,6	86,6	95,4	95,4	97,4	97,4
Gross weight kg	45,0	46,0	75,0	75,0	75,0	75,0	94,0	94,0	108,0	108,0	109,0	109,0



Spiral Machine												
Model	IMR 5	IMR 10	IMR 15	ITR 15	IMR 20	ITR 20	IMR 30	ITR 30	IMR 40	ITR 40	IMR 50	ITR 50
Dough weigh kg	5,0	8,0	12,0	12,0	17,0	17,0	25,0	25,0	35,0	35,0	42,0	12,0
Capacity	7,0	10,0	16,0	16,0	22,0	22,0	32,0	32,0	41,0	41,0	48,0	16,0
Dough/ hour kg	29,0	35,0	48,0	48,0	56,0	56,0	88,0	88,0	102,0	102,0	128,0	48,0
Bowl diameter cm	24,0	26,0	32,0	32,0	36,0	36,0	40,0	40,0	45,0	45,0	45,0	32,0
Power supply volt	230	230	230 400	230 400	230 400	230 400	230 400	230 400	230 400	230 400	230 400	230 400
Single-phase motor power KW (volt230) hp	0,37 0,5	0,37 0,5	0,75 1,0	0,75 1,0	0,75 1,0	0,75 1,0	1,1 1,5	1,1 1,5	1,1 1,5	1,1 1,5	1,5 2,0	1,5 2,0
Single-phase motor power KW (volt400) hp	- -	- -	0,75 1,0	0,75 1,0	0,75 1,0	0,75 1,0	1,1 1,5	1,1 1,5	1,1 1,5	1,1 1,5	1,5 2,0	1,5 2,0
Machine sizes Dimension cm	L 38,5 P 67,0 H 67,5	L 38,5 P 67,0 H 67,5	L 38,5 P 67,0 H 67,5	L 38,5 P 67,0 H 67,5	L 38,5 P 67,0 H 72,5	L 38,5 P 67,0 H 72,5	L 42,4 P 73,5 H 80,5	L 42,4 P 73,5 H 80,5	L 48,0 P 80,5 H 82,5	L 48,0 P 80,5 H 82,5	L 48,0 P 80,5 H 82,5	L 48,0 P 80,5 H 82,5
Packing dimensions cm	L 73,5 P 41,5 H 69,5	L 73,5 P 41,5 H 69,5	L 73,5 P 41,5 H 79,5	L 73,5 P 41,5 H 79,5	L 73,5 P 41,5 H 79,5	L 73,5 P 41,5 H 79,5	L 76,5 P 47,5 H 88,5	L 76,5 P 47,5 H 88,5	L 82,5 P 54,0 H 93,5	L 82,5 P 54,0 H 93,5	L 82,5 P 54,0 H 93,5	L 82,5 P 54,0 H 93,5
Volume m3	0,21	0,21	0,24	0,24	0,24	0,24	0,32	0,32	0,42	0,42	0,42	0,42
Net weight kg	58,0	56,0	71,5	71,5	81,0	81,0	94,6	94,6	114,0	114,0	122,0	122,0
Gross weight kg	60,0	60,0	77,5	77,5	85,0	85,0	103,0	103,0	121,0	121,0	129,0.	129,0.



MITTAL INTERNATIONAL

Head Office : 7, Netaji Subhash Marg, Darya Ganj, New Delhi-110 002, Ph. : 23271810, 23279639, 23278741, 23242500-1-2-3, Fax : 011-23271218
E-mail : mitalin@vsnl.com, sales@mitalin.com, Website : www.mitalin.com

Branch Offices :
MUMBAI OFFICE : 171, Udyog Bhawan, Sonawala Road, Goregaon (E), Mumbai-400063 Ph. : 26861938, 26863195 Fax : 26867171, E-mail : mittalinternational@mtnl.net.in
CHENNAI OFFICE : E.W.S. No. 1729, 1st Main Road, Vasantha Colony, Off. 18th Main Road, Anna Nagar West, Chennai-600040, Tel. : 044-43831150, E-mail : chennaioffice@mitalin.com